Double Shell Closure with Support Ribs Serial No.: 09/876,336 Atty. Docket #: CG-838

IN THE CLAIMS

1-21. (canceled)

٥

- 22. (previously presented) A container closure comprising:
- a. a top, having an interior surface and an exterior surface;
- b. an annular outermost skirt, depending from and being centered on the interior surface of said top, said outermost skirt having a first face which faces inward toward the center of said outermost skirt, a second face which faces outward from said outermost skirt, a top edge which abuts said top, and a bottom edge, and said outermost skirt having a first diameter at the top edge of the outward face and a second diameter at the bottom edge of the outward face wherein said top diameter is greater than said bottom diameter causing said outermost skirt to have a frustoconical configuration on the exterior surface;
- c. an annular innermost skirt, depending from and being centered on the interior surface of said top, said innermost skirt having a first surface which faces inward toward the center of the skirt and a second surface which faces outward toward said outermost skirt;
- d. at least one thread attached to the inward facing surface of said innermost skirt; and
- e. at least one rib, depending from said top and extending radially along said top to said outermost skirt, said rib also being attached to the outward facing surface of said innermost skirt and said inward face of said outermost skirt;
- f. said at least one rib having a first axial dimension at said innermost skirt and a second axial dimension at said outer skirt, said first axial dimension being less than said second axial

Double Shell Closure with Support Ribs Serial No.: 09/876,336 Atty. Docket #: CG 838

dimension.

- 23. (previously presented) The closure of claim 22 wherein said innermost skirt defines a length and at least part of said rib is the same length as said innermost skirt.
- 24. (previously presented) The closure of claim 22 wherein said outermost skirt defines a length and at least part of said rib is the same length as said outer skirt.
- 25. (canceled)
- 26. (previously presented) The closure of claim 22 wherein said outer skirt defines a length and at least part of said rib is shorter than the length of said outermost skirt.
- 27. (previously presented) The closure of claim 22 wherein said innermost skirt has a diameter that is less than the bottom diameter of said outermost skirt and said closure further includes an annular flange depending from the interior surface of said top and being centered on the interior surface of said top, said flange having a diameter that is smaller than the diameter of said innermost skirt.

28 - 36 (canceled)

37. (previously presented) A container closure, comprising:
a top wall and an outer skirt having a first diameter depending from said top wall;
an inner skirt having a second diameter smaller than said first diameter depending from said top wall;

a plurality of ribs depending from said top wall along an inner face of said outermost skirt and extending to an outer face of said innermost skirt;

said outer skirt being tapered and being frusto-conical in shape;

Double Shell Closure with Support Ribs Serial No.: 09/876,336 Atty, Docket #: CG 838

each of said plurality of ribs being opposite an outer skirt rib positioned on said outer face of said outer skirt;

each of said plurality of ribs being substantially L-shaped.

- 38. (previously presented) The container closure of claim 37, each of said plurality of ribs having a first edge having a length equal to said outermost skirt.
- 39. (previously presented) The container closure of claim 37, each of said plurality of ribs having a second edge having a length equal to said innermost skirt.
- 40. (canceled)
- 41. (previously presented) The container closure of claim 37, said rib having a tapered lower edge.
- 42. (previously presented) The container closure of claim 37, further comprising an annular flange depending from and centered on an interior surface of said top wall, said annular flange having a diameter less than said innermost skirt.